NEOTEX®
CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS & SALES CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600
Industrial Area Mandra
Athens, Greece
T. +30 210 5557579

NORTHERN GREECE BRANCH
Ionias str., GR 57009
Kalochori Thessaloniki, Greece
T. +30 2310 467275

www.neotex.gr • export@neotex.gr

Declaration of Performance - DoP No.: 4950-14

Neoproof® Polyurea R

CE

1.	**Unique identification code of the product type:**	**Neoproof® Polyurea R**
2.	**Intended use/es:**	Surface protection products - Coating
3.	**Manufacturer:**	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece
4.	**Authorized representative:**	---
5.	**System/s of Assessment and Verification of Constancy of Performance (AVCP):**	2+
6a.	**Harmonized standard**	EN 1504-2:2004
	Notified body/ies:	The notified body, ***DEDAL*** *Attestation & Certification, Bulgaria, 8230 Nesebar Mladost #50*, with c*ertification no. 1922*, carried out the initial inspection of the factory and the production control at the factory and conducts continuous monitoring, evaluation, and approval of the production control under system 2+ and issued: ***Certificate of Conformity of the production control at the factory*** ***No. 1922-CPR-0386***
6b.	**European assessment document:**	---
	European technical assessment*:*	---
	Technical assessment body*:*	---
	Notified body/ies:	---

NEOTEX
CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS & SALES CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600
Industrial Area Mandra
Athens, Greece
T. +30 210 5557579

NORTHERN GREECE BRANCH
Ionias str., GR 57009
Kalochori Thessaloniki, Greece
T. +30 2310 467275

www.neotex.gr • export@neotex.gr

Declaration of Performance - DoP No.: 4950-14

Neoproof® Polyurea R

CE

7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Water vapour permeability	Class II	**EN 1504-2:2004**
Adhesion strength	≥1.5N/mm^2	
Capillary absorption and permeability to water	W<0.1Kg/m^{2}h$^{0.5}$	
Permeability to CO_2	S_D>50m	
Reaction to fire	Class E	
Dangerous substances	Complies with 5.3	

8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX S.A.
HEADQUARTERS: V. MOIRA STR., GR 19 600
INDUSTRIAL AREA MANDRA - GREECE
TEL.:+30 210 5557579 VAT NUMBER: EL 094029945
PRN: 4164
www.neotex.gr - e-mail: export@neotex.gr

Lampros Ntoumos

Technical Director

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS & SALES CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600
Industrial Area Mandra
Athens, Greece
T. +30 210 5557579

NORTHERN GREECE BRANCH
Ionias str., GR 57009
Kalochori Thessaloniki, Greece
T. +30 2310 467275

www.neotex.gr • export@neotex.gr

CE

1922

NEOTEX S.A.
V.Moira str., P.O. Box 2315
GR 19600 Industrial Area Mandra, Athens, Greece

16

1922-CPR-0386

DoP No.: 4950-14

EN 1504-2

Neoproof® Polyurea R

Surface protection products

Coating

Water vapour permeability	Class II
Adhesion strength	≥1.5N/mm^2
Capillary absorption and permeability to water	W<0.1Kg/m^{2}h$^{0.5}$
Permeability to CO_2	S_D>50m
Reaction to fire	Class E
Dangerous substances	Complies with 5.3